Installation Instruction

SKU: X-H(V)-04/X-H(V)-06 Product: Vertical bike rack



List of installation accessories					
Code	Spare parts Name	picture	QTY		
A	Vertical support Tube with damper		1		
В	Hitch Wedge Bar		1		
С	Lower tire crossbar		1		
D	Upper tire cradle crossbar		1		
Е	Tire Cradle		4		
F	Lower Tire plate		4		
G	Number plate		1		

AIX Vertical Bike Rack

www.xcarrack.com info@xcarrack.com Η Anti-wobble Hitch Lock 1 M12*90 Ι 3 Black cylindrical head bolt J M8*65 **26** Black flat round head bolt K M8*15 **12** Black flat round head bolt L M6*12 3 Black flat round head bolt M M10*80 5 Black flat round head bolt N M12 Black nut 3 M10 Black nut 5 O P M8 Black nut **25** V M8*16*1.5 Flat washer **12** M10*20*1.5 Flat washer R 4

AIX Vertical Bike Rack

S M12*22*2 Flat washer

T M10 Spring washer

U M12 Spring washer

2


4

List of other accessories						
ITEM NO.	Designation	QTY.	Remarks			
1	M12 Allen key	1	Own			
2	M10 Allen key	1	Own			
3	M8 Allen key	1	Own			
4	M6 Allen key	1	Own			
5	wrench	1	Own			

Assembly steps

Step 1






Step 2 В I N S U Connect the B hitch wedge bar and A vertical column with screws

Step 3




Step 4




Step 5 D E J P Ε D

Step 6



Step 7



Important Usage Notice

This product's standard size is not compatible with tires exceeding 3" in width. For parking bicycles with tires wider than 3", please purchase the following accessories:

No.	Model	Name	Picture
1	X-H(V)-Cradle (128)	Cradle of vertical bike rack -128mm	
2	X-H(V)-Tplate(128)	Lower tire Plate-128mm	

Weight Limitations

Single parking space capacity: 35 kg (77 lbs) Total product capacity: 120 kg (265 lbs)

When using this rack, always verify that your bicycle's weight does not exceed individual or total limits. Overloading may cause structural failure and result in injury or property damage.

For optimal safety, we recommend: Weighing your bicycle before use

Distributing weight evenly across parking spaces

END